

ABC®Metals, Inc.

UNCOIL THE POWER OF ABC METALS Contact us Toll Free at 800-238-8470

POST OFFICE BOX 300 500 W. CLINTON STREET LOGANSPORT, INDIANA 46947 FAX 574-753-6110 12124 Rojas Drive EL PASO, TEXAS 79936 FAX 915-845-6403 1901 MOZELLE STREET PHARR, TEXAS 78577 FAX 956-782-7693

April 14th, 2016

Subject: Compliance to RoHS, GADL, TSZ0001G Restrictions on Substances of Concern.

We confirm that our company has received and reviewed the EVL/GADL and TSZ0001G standards for restricted and prohibited use of substances of environmental concern.

The key raw material suppliers of ABC® Metals have attested to full compliance of the above mentioned standards. ABC has also performed audits and 3rd party testing, using accredited laboratories to test our key alloys and products for the presence of any listed substance of concern compounds and elements. ABC® Metals verified that our products are in full compliance to the reference standards, being measurably absent of or less than the detection limits, for any of the SoC elements. See laboratory test report and data on Toyota FORM 2 11-2 SoC ESS which is posted on our website, and available to any individual or company wanting to have a copy of these compliance tests.

ABC®Metals is a registered user with the International Material Data System (IMDS), and is able to provide such information upon request.

If you have any questions or comments, please do not hesitate to contact an ABC Metals representative at the phone number listed above.

Regards,

Daniel Muddell
Signature

Dan Kendall
President
ABC®Metals Inc.

danken@abcmetals.com

Signature

Dee Butz Corp. Director of QA MPI Corporation

deebut@abcmetals.com

Signature

Mike Englert
Mgr. Facilities & Environmental
ABC Metals and HTI Inc.

mikeng@callhti.com

Delivery Part Information		Sign / APPROV	ER APPROVER	ORIGNATO													
Vehicle Code Delivery Part No. Delivery Part Name Delivery Supplier N		Sign / Date	4/19/2016 Mile English 4/19/	2016 SwA	4/10/2016												
		Name / Des Kandell /		of Dog Butz / Director		ease reference TS	SZ0001G to obtain	ain allowa	hla limite								
		Title Basis for SoC Judgment	Environmental and Faci	lites Dee Butz / Director	of Quality 776	sase reference 10.	DECOUTE TO OBTAI	iiii anowai	bie iiiiits.								
	Pb Cd Hg				Cr+6 PBDE PBB Asbestos Deca-BDE					DE	HBCD PFOS			3			
Sub-Component Part Name Sub-Component Part No.	Supplier Name	Method Result	Method Result M	Method Result	Method	Result		Result	Method Result	Method	Result	Method	Result	Method	Result	Method	Judgment Result
C500 Series Tin Bronze Alloy Sheet/Strip/Plate C500 Series Tin Bronze Alloy Sheet/Strip/Plate	ABC Metals Inc.	1 < 14 ppm	1 < 3 ppm	2 < 1 ppm	1	127 ppm	3	N/A	3 N/A	3	N/A	3	N/A	3	N/A	3	N/A See Attached
Method # Machine	RoHS Limit:	1000 ppm	1000 ppm	100 ppm		1000** ppm	10	000 ppm	1000 ppm								
1 Atomic Absorption Spectrometer					**The analysis	performed on these											
2 Cold Vapor Atomic Absorbtion						ed total chromium and cific to hexavalent											
3 N/A					chromium (Cr+6).	. Total chromium would um in a non-oxidized											
					state (Cr+0) ii	in addition to Cr+6.											
					Therefore, Cr+6 i	in the materials, if any, sed the total chromium											
						ontent.											
			+														
										-							
					1										-		
					1												
					1					-							
								t									
					1												
					1												
					1												
					-												
					-					-							
					-												
Judgment O Meets requirements X	Does no	ot meet requirements	 		1	1										Form	2.11-2: Issue 5, Rev. E
STIDDLIED UC		*	1.														



Mr. Brennan Perez 2016-030482A Lab No.: **Inception: ABC Metals** March 29, 2016 500 West Clinton Report Date: April 11, 2016 April 21, 2016 Logansport, IN 46947 Amended:

PO No.: LP001978

Project: Compositional Analysis (RoHS).

Sample(s) Received:

Eight (8) sections of metalic strip idenified in the reults section on page 2.

Procedure:

Approximately 1 gram was sectioned from each sample. The sections were digested in trace metal grade acid(s) then diluted to 50 ml times using ASTM Type 1 purified water. For lead, cadmium and chromium the prepared solutions were diluted an additional 10 times then analyzed via atomic absorption (AA) per a modified SM3111B procedure. For mercury, the prepared solutions were diluted an additional 7 times then analyzed per EPA 245.1.

Requirements:

Lead 0.1% by weight (1000 ppm)

Mercury 0.1% by weight (1000 ppm)

Cadmium 0.01% by weight (100 ppm)

Hexavalent Chromium 0.1% by weight (1000 ppm)

Note: It is our policy to keep copies of reports for seven years. The data is kept on file for up to seven years. Samples (if applicable) are kept for three weeks. Samples that are hazardous will be returned to the client. If this policy poses a difficulty, please contact us to make other arrangements. If reproduced, our report must be reproduced completely. Any unauthorized alteration of this report invalidates the content.

Page 1 of 3

ABC Metals

Lab No.: 2016-030482A

April 21, 2016

Results:

It should be noted that in the table below any result listed as less than (<) were below the limits of detection for the analysis performed.

Sample	Compositional Results in ppm									
Sample	Pb	Hg	Cd	Total Cr*						
C102 High-Copper	212	<0.364	<4.73	<104						
C260 Brass	57.4	<0.342	<4.45	<97.8						
G1008 Cold Rolled Low Carbon Steel	<15.5	<0.298	5.42	277						
C7025 Copper Nickel	<14.3	<0.560	<3.59	<78.9						
C110 High-Copper	15.2	<0.259	<3.37	<74.1						
C519 Phosphor Bronze	<13.6	<0.261	<3.39	127						
C655 Silicon Bronze	<15.4	0.565	<3.84	250						
C425 Tin Brass	<17.3	<0.333	<4.32	<95.1						
RoHS Limit	1000	1000	100	1000**						

^{*}The analysis performed on these samples detected total chromium and was not specific to hexavalent chromium (Cr^{+6}). Total chromium would include chromium in a non-oxidized state (Cr^{+0}) in addition to Cr^{+6} . Therefore, Cr^{+6} in the materials, if any, could never exceed the total chromium content.

Disposition:

All samples conform to RoHS limits for lead, mercury, cadmium and hexavalent chromium.

Note: It is our policy to keep copies of reports for seven years. The data is kept on file for up to seven years. Samples (if applicable) are kept for three weeks. Samples that are hazardous will be returned to the client. If this policy poses a difficulty, please contact us to make other arrangements. If reproduced, our report must be reproduced completely. Any unauthorized alteration of this report invalidates the content.

Page 2 of 3

^{**}The RoHS limit is for hexavalent chromium (Cr⁺⁶) not total chromium.

ABC Metals

Lab No.: 2016-030482A

April 21, 2016

Additional Comments:

While no testing was conducted for asbestos, PBB, PBDE, Deca-BDE, HBCD or PFOS it would be highly unlikely for any to be present within the materials. PBB, PBDE, Deca-BDE, HBCD and PFOS are organic compounds used as flame retardants or surfactants (PFOS). These compounds have boiling points well below the melt temperatures of the alloys tested and would have been evolved or decomposed when the alloys were in a molten state. Similarly, asbestos is decomposed at temperatures between 1832-2282° F (1000-1250° C). For comparison purposes the melting point of pure copper is 1984° F (1085° C).

Respectfully Submitted,

Scientific Control Laboratories, Inc.

Christopher Catalina

Metallurgical Services, Ext. 41

ccatalina@sclweb.com

Note: It is our policy to keep copies of reports for seven years. The data is kept on file for up to seven years. Samples (if applicable) are kept for three weeks. Samples that are hazardous will be returned to the client. If this policy poses a difficulty, please contact us to make other arrangements. If reproduced, our report must be reproduced completely. Any unauthorized alteration of this report invalidates the content.